HYBRID WET C-BOND

DIAMOND TOOLING SERIES

Hybrid 3" Velcro Puck Diamond Tools for Wet Grinding / Power Trowel

Increase efficiency with the industry's most effective and economical hybrid series, now with a new and improved formula!

The SASE Hybrid Wet C-Bond Series boasts a new and improved formula that includes an exclusive, proprietary copper matrix resulting in up to 300% increase in tooling life and easy and effective transitioning between metal and resin bond steps.

FEATURES

- New and improved formula including an exclusive, proprietary copper matrix
- Part of SASE HydraTrowel System for use with ride-on power trowel equipment
- Easy and effective transitioning between metal and resin bond steps
- Increased efficiency with up to 300% increase in tooling life*
- Can skip grinding steps or be used as a starting point for a 3 to 4 step economical, salt and pepper or cream finish floor
- Designed for wet grinding applications
- Lower grits can remove most cure and seals



300% Increase in tooling life

*When compared to previous hybrid wet series.

OLD FORMULA



NEW!



HOL.905218 SASE 3" Puck Flex Plate

HYBRID WET C-BOND DIAMOND TOOLING SERIES



SASE Hybrid Wet C-Bond Series Tooling Guide

	Item #	Product Name	Description
1-800-522-2606 WET ONLY C #30	HOL.300600	Hybrid Wet C-Bond Series 30 grit - Lime 3" Puck	This tool is designed for wet operation and can be used to remove cure and seal off of new concrete and/or be the initial starting point to expose salt and pepper aggregate. It can also be used to remove 25 grit metal scratches.*
1-800-622-2606 WET ONLY C #50	HOL.300601	Hybrid Wet C-Bond Series 50 grit - Grey 3" Puck	This tool is designed for wet operation and can be used to remove cure and seal off of new concrete and/or be the initial starting point to expose salt and pepper aggregate. It can also be used to remove 40 grit metal scratches.*
SE COMPANA 1-800-522-2606 WET ONLY C #100	HOL.300602	Hybrid Wet C-Bond Series 100 grit - Black 3" Puck	This tool is designed for wet operation and can be used to remove thin cure and seal off of new concrete and/or be the initial starting point to expose little to no aggregate (cream finish). It can also be used to remove 80 grit metal scratches and removal step after a grout coat application.*
1-800-522-2606 WET ORLY C #200	HOL.300603	Hybrid Wet C-Bond Series 200 grit - Blue 3" Puck	This tool is designed for wet operation and can be used to remove 100 grit hybrid and/or 150 grit metal scratches.*
1-800-522-2806 WET OILY C #400	HOL.300604	Hybrid Wet C-Bond Series 400 grit - Red 3" Puck	This tool is designed for wet operation and can be used to remove 200 grit hybrid scratches and in some cases, remove 100 grit hybrid scratches.*

*All concrete floors and project specifications are unique. Use these descriptions as a guide and test small areas before proceeding with full scale operation.





WORKS GREAT UNDER FLOOR GRINDERS & POWER TROWELS!



SASE Company, LLC.2475 Stock Creek BLVD | Rockford, TN 37853
Phone: 1 (800) 522-2606 | Fax: (865) 745-4110
Web: www.SASECompany.com

© 2020 SASE Company, LLC. All Rights Reserved - v2020-01-23 | 1045